

가

Last update: 2025/03/19

가 1

가

- xFrame5 HTML JS index.html, index.js 가 ,
index.js _xf_param
- xFrame5 xFrame5@Admin "xadmin"
- xFrame5 xFrame5@DevStudio "devstudio"

- index.js _xf_param factory
- 가 가 ,
factory.gethtmlparam API

Name	Data Type	Default Value	Valid values	Sample Value	Description
APPNAME	STRING			UI	UI • APPNAME • UI
APPID	STRING			SOFTBASE_UI	UI ID • ID • APPID • UI
LICENSE_KEY	ARRAY	((["KEY_1", "KEY_2"]		• Domain IP (IP) • "http/https" • 가 • / • "127.0.0.1", "localhost" • factory.isvalidlicensekey API
DBMS_CHARSET	STRING	UTF-8	UTF-8, EUC-KR		• DBMS • "UTF-8" 3 • "UTF8MB4" 4 • 2
CHECK_4BYTE_CHAR	BOOL	false	true, false		• 4 • UTF-8 4 • true
ENGINEURL	STRING			./xf5	• XFRAME5 URL • , index.html
ENGINEHTMLURL	STRING			./index.html	• XFRAME5 HTML URL • , index.html

Name	Data Type	Default Value	Valid values	Sample Value	Description
ENGINEMODE	STRING	RELEASE	RELEASE, DEBUG	RELEASE	RELEASE RELEASE: DEBUG: js
RUNMODE	STRING	RELEASE	DEBUG, RELEASE	RELEASE	“Source” DEBUG: RELEASE:
CHECK_SCREENURL	BOOL	false	true, false		HTTP HEAD true: false:
SCREENBASEURL	STRING			./project/screen	URL index.html xadmin “./version/screen/prod/master/screen”
IMAGEBASEURL	STRING			./project/image	URL index.html xadmin “./version/screen/prod/master/image”
PICKLISTBASEURL	STRING			./project/picklist	URL index.html xadmin “./version/screen/prod/master/picklist”
STYLEBASEURL	STRING			./project/style	URL index.html xadmin “./version/screen/prod/master/style”
COMMONMODULEBASEURL	STRING			./project/screen /common_module	URL (function index.html COMMONMODULE_LOADTYPE 0 (script) common_module.lst xadmin “./version/screen/prod/master/screen/common_module”
IMPORTMODULEBASEURL	STRING			././project/screen /common_module	(import) URL xf_engine.min.js URL COMMONMODULE_LOADTYPE 1 (import) common_module.lst xadmin “./version/screen/prod/master/screen/common_module”
COMMONMODULE_LOADTYPE	INT	0	0, 1		0: script(, JavaScript , iframe) 1: import(JavaScript import)

Name	Data Type	Default Value	Valid values	Sample Value	Description
COMMONXDATASETBASEURL	STRING			./project/screen /common_xdataset	<ul style="list-style-type: none"> URL , index.html common_xdataset.lst xadmin "/version/screen/prod/master/screen/common_xdataset"
BUILD_SCREEN_MODE	BOOL		false		<ul style="list-style-type: none"> BUILD_SCREENBASEURL
BUILD_SCREENBASEURL	STRING			./project/build/screen'	<ul style="list-style-type: none"> URL , SCREENBASEURL
BUILD_COMMONMODULE_MODE	BOOL		false		<ul style="list-style-type: none"> BUILD_SCREENBASEURL
BUILD_COMMONMODULEBASEURL	STRING			./project/build/screen/common_module	<ul style="list-style-type: none"> URL , COMMONMODULEBASEURL
BUILD_IMPORTMODULEBASEURL	STRING			././project/build/screen/common_module	<ul style="list-style-type: none"> COMMONMODULE_LOADTYPE 가 1 URL , IMPORTMODULEBASEURL
AMCHARTS5BASEURL	STRING			./xf5/ext/amcharts5	<ul style="list-style-type: none"> amcharts5 URL , index.html
XDATASET_BASEURL	STRING				<ul style="list-style-type: none"> XDataSet XTranMap URL URL
XDATASET_MAX_LENGTH_UNIT	INT	0	0, 1	0	<ul style="list-style-type: none"> length 0: byte(), / DBMS_CHARSET 1:
XDATASET_SETDATA_CHECK_MAXLENGTH	INT	0	0, 1, 2	0	<ul style="list-style-type: none"> length length 1 XDATASET_MAX_LENGTH_UNIT 0 가 0: 1: api, setdata API 2: all, (setdata API XTran)
USE_BIG_NUMBER	BOOL	false	true, false		
MODULE_USE_BIG_NUMBER	BOOL	false	true, false		(xf5/ext/lib/big.min.js)
COMMONMODULE_EXTLIB	OBJECT	undefined			<pre>COMMONMODULE_LOADTYPE 1(import) KEY: VALUE: URL (URL HTML COMMONMODULE_EXTLIB COMMONMODULE_EXTLIB: { // SYSUtil 2 URL 'SYSUtil': ['./xf5/ext/lib/hangul.min.js', './xf5/ext/lib/big.min.js'], // SYSLog 1 URL 'SYSLog': ['./xf5/ext/lib/hangul.min.js'], // SYSLog 1 URL 'SYSVar': ['https://cdnjs.cloudflare.com/underscore-min.js'] },</pre>
USE_TRANMAP_ATTR	BOOL	true	true, false		

Name	Data Type	Default Value	Valid values	Sample Value	Description
MAP_INPUTTYPE_SHOWAPPLY	BOOL	true	true, false		<ul style="list-style-type: none"> Show/Hide true 가
MAP_INPUTTYPE_APPLYDISABLED	BOOL	true	true, false		<ul style="list-style-type: none"> false
MAP_APPLY_CLEARITEMPROP	BOOL	true	true, false		<ul style="list-style-type: none"> false
USE_PREFIX_STYLE	BOOL	false	true, false		<ul style="list-style-type: none"> '_XF_GRID_COLUMN_DATA' ID
ALLOWED_JS_LIST	ARRAY	[]			<ul style="list-style-type: none"> loadjs API 가 JavaScript JavaScript가 가
MAINFRAMESCREEN	STRING			/SYS/StartMain	<ul style="list-style-type: none"> ID devstudio Sample Value SCREENBASEURL + MAINFRAMESCREEN + ".xml"
SHOW_CONSOLETRACE	BOOL	false	true, false		
POPOP_CONSOLETRACE	BOOL	false	true, false		
CONSOLETRACE_SHOWLOG	BOOL	true	true, false		
CONSOLETRACE_SHOWEVENT	BOOL	true	true, false		
CONSOLETRACE_SHOWTIMEREVENT	BOOL	true	true, false		
CONSOLETRACE_SHOWEVENTPARAM	BOOL	true	true, false		
CONSOLETRACE_SHOWTRAN	BOOL	false	true, false		XTRAN tran
CONSOLETRACE_SHOWINNERCOLUMN	BOOL	false	true, false		xdataset
CONSOLETRACE_SHOWXDATASETMAXROW	INT	100			xdataset
CONSOLETRACE_USEBROWSERCONSOLE	BOOL	false	true, false		
MAINLOADSTATUS_SHOW	BOOL	false	true, false		<ul style="list-style-type: none"> true: false:
MAINLOADSTATUS_AUTOHIDE	BOOL	true	true, false		<ul style="list-style-type: none"> MAINLOADSTATUS_SHOW 가 true true: false: hidemainloadstatus API
EVENTFIRE_BEFORE_SCREENONLOAD	BOOL	true	true, false		<ul style="list-style-type: none"> on_load 가 false true: on_load false: on_load 가
EVENTFIRE_SYNC_SCREENONLOAD	BOOL	false	true, false		<ul style="list-style-type: none"> on_laod 가 true true: 가 on_load 가 false: on_load 가

Name	Data Type	Default Value	Valid values	Sample Value	Description
EVENTFIRE_SYNC_PORTLETONLOAD	BOOL	false	true, false		<ul style="list-style-type: none"> on_load 가 true true: 가 on_load 가 false: on_load 가
USE_CACHE	BOOL	true	true, false		AJAX Cache ()
CACHE_TYPE	INT	0	0, 1, 2, 3, 4		USE_CACHE 가 true 0: 1: HTTP HEAD () 2: HTTP HEAD () 3: () 4: ()
USE_PICKLIST_CACHE	BOOL	true	true, false		PickList AJAX Cache () PickList true , AJAX Cache CACHE_TYPE 가
USE_METADATA_CACHE	BOOL	false	true, false		AJAX Cache () true , AJAX Cache CACHE_TYPE 가
MOUSERCLICK_FIELD_FOCUS	BOOL	true	true, false		
MOUSECLICK_DISABLEFIELD_FOCUS	BOOL	false	true, false		/ true 가 , 가
KEYMAP_CLEAR_VALUE	ARRAY	[]		[27]	(27: ESC)
KEYMAP_FOCUS_NEXT	ARRAY	[]		[13]	(13:)
KEYMAP_FOCUS_PREV	ARRAY	[]			
KEYMAP_TRIPLE_ZERO	ARRAY	[]		[113]	"000" (113: ".")
KEYMAP_BUTTON_CLICK	ARRAY	[32]			가 (32: SPACE)
KEYMAP_POPUP_CLOSE	ARRAY	[27]			/ / (27: ESC)
KEYMAP_ALLOW_FUNCKEY	ARRAY	[]			(112: F1 ~ 123: F12) F11: , F12:
KEYMAP_MULTILINE_SELECTALL	ARRAY	[]			
MULTILINE_NEWLINE	INT	2	0, 1, 2		0: ALT + ENTER(EXCEL) 1: SHIFT ENTER 2: ENTER
MULTILINE_TAB	INT	0	0, 1, 2		Tab 0: none 1: SHIFT TAB 2: TAB
CALENDAR_TODAY	STRING		20200615		YYYYMMDD PC 가 factory get/setcalendartoday API
CALENDAR_TODAYBAR_CLICKTYPE	INT	1	1, 2		1: move date(), 2: select date,

Name	Data Type	Default Value	Valid values	Sample Value	Description
CALENDAR_CUSTOMCLASS	STRING				CSS CSS .html CSS
BROWSER_AUTOCOMPLETE	INT	1	1,2		1: on () 2: off () 3: on-password ()
CHECKBOX_FOCUSRECT_TYPE	INT	1	1,2		(drawfocusrect true .) 1: box () 2: text ()
RADIOBUTTON_FOCUSRECT_TYPE	INT	1	1,2		(drawfocusrect true .) 1: box () 2: text ()
RADIOBUTTON_FOCUS_SELECTGROUP	BOOL	false	true, false		true: 가 가 false:
PC_CLICK_SETFOCUS	BOOL	false	true, false		PC click_setfocus false: none true: set(true)
PC_CLICK_SETFOCUS_TARGET	ARRAY	[]			PC click_setfocus (getcontrolkind API) : [XFD_CTRLKIND_TABLEVIEW, XFD_CTRLKIND_TAB, XFD_CTRLKIND_PANEL]
MOBILE_CLICK_SETFOCUS	BOOL	true	true, false		click_setfocus false: none true: set(true)
MOBILE_POPUPMENU_SHOW	BOOL	true	true, false		
MOBILE_SCREEN_AUTOSIZE	BOOL	true	true, false		auto width_type, height_type
DATEPICKER_MOBILEMODE_APPLY	INT	1	1, 2		1: none(), PC 2: apply, , calendar_size 4: xlarge
DATEPICKER_CALENDAR_CUSTOMCLASS	STRING				CSS CSS .html CSS

API COMBOBOX_SETCODE_CHECKTYPE (1:set(), 2:no-set)가 (0 ,)

COMBOBOX_SETCODE_CHECKTYPE	INT	1	1, 2		API 1: set(), 2: no-set, , return false
COMBOBOX_MOBILEMODE_APPLY	INT	1	1, 2, 3		1: none(), PC 2: apply(popup), 3: apply(select), SELECT
XTRAN_DATAENCODING	BOOL	false	true, false		XDataSet BASE64
XTRAN_ENCRYPT	STRING		"" , "AES"		XDataSet / /
XTRAN_XSSENCODING	BOOL	false	true, false		XDataSet

XTRAN_CLEARINNERCOLUMN	BOOL	false	true, false	XDataSet CLEAR
XTRAN_TIMEOUT	INT		3600000	XDataSet (: ms)
XTRAN_COMPRESS	BOOL	false	true, false	XDataSet • true: gzip • false:
XTRAN_DATAFORMAT	STRING	"json"	"json", "xml"	XDataSet • "json": JSON • "xml": XML "xml" xdataset5.jar FrameWork XML "json" "xml"
XTRAN_SENDDATAKEY	STRING	"XDATASETS5"	"XDATASETS5", "	XDataSet POST • "XDATASETS5": XDataSet JSON • " " : XML " " xdataset5.jar FrameWork XML
XTRAN_URLENCODING	BOOL	true	true, false	XDataSet encodeURIComponent
XTRAN_JSONSENDDATAFUNC XTRAN_JSONRECVDATAFUNC	STRING			XDataSet XTRAN_DATAFORMAT "json" " " " " xdataset5.jar " Framework JSON XTRAN_JSONSENDDATAFUNC XTRANMAP_ID, JSON 가 XTRAN_JSONSENDDATAFUNC JSON XTRAN_JSONRECVDATAFUNC XTRANMAP_ID, JSON XTRAN_JSONRECVDATAFUNC JSON
XTRAN_XMLSENDDATAFUNC XTRAN_XMLRECVDATAFUNC	STRING			XDataSet XTRAN_DATAFORMAT "xml" " " " " xdataset5.jar " Framework XML XTRAN_XMLSENDDATAFUNC XTRANMAP_ID, JSON 가 XTRAN_XMLSENDDATAFUNC XTRAN_XMLRECVDATAFUNC XTRANMAP_ID, JSON XTRAN_XMLRECVDATAFUNC JSON
XTRAN_DATALOG	INT	0	0, 1, 2, 3	XDataSet • 0: • 1: • 2: • 3: /
XTRAN_DATALOG_SHOWTYPE	INT	0	0, 1, 2	XDataSet • 0: • 1: • 2: CALLBACK_XTRAN_DATALOG
XTRAN_OUTPUTCOLUMNMODE	INT	0	0, 1	XDataSet • 0: dynamic - XTranMap Output 가 • 1: fixed - XTranMap Output • API: get/setxtranmapoutputcolumnmode
XTRAN_WITHCREDENTIALS	BOOL	true	true, false	XDataSet withCredentials AJAX

FOCUS_ROTATE	BOOL	false	true, false	<ul style="list-style-type: none"> • true • 가 • tabstop false
TRAN_BASEURL	STRING			<ul style="list-style-type: none"> • requesttran API URL
TRAN_WITHCREDENTIALS	BOOL	true	true, false	<ul style="list-style-type: none"> • requesttran API AJAX withCredentials
CALLBACK_REQUESTTRAN_SENDDATAFUNC CALLBACK_REQUESTTRAN_RECVDATAFUNC	STRING			<ul style="list-style-type: none"> • requesttran API • " " " " FrameWork • xdataset5.jar • CALLBACK_REQUESTTRAN_SENDDATAFUNC , TRANMAP_ID가 • CALLBACK_REQUESTTRAN_SENDDATAFUNC settranmaptraninfo API • CALLBACK_REQUESTTRAN_RECVDATAFUNC , TRANMAP_ID • CALLBACK_REQUESTTRAN_RECVDATAFUNC • (Global Callback 가).
FOCUS_ROTATE	BOOL	false	true, false	<ul style="list-style-type: none"> • true • 가 • tabstop false
MODALPOPUP_MINBUTTON_SHOW	BOOL	false	true, false	
MODALPOPUP_MAXBUTTON_SHOW	BOOL	true	true, false	
MODALPOPUP_MOVE_OVERFLOWX	BOOL	false	true, false	가
MODALPOPUP_MOVE_OVERFLOWY	BOOL	false	true, false	가
MODALPOPUP_TITLEBAR_HEIGHT	INT	30	20	
ANIMATE_TYPE_MESSAGEBOX	INT	1	0, 1	<ul style="list-style-type: none"> • screen.messagebox API Animation • 0: none Animation • 1: basic Animation
ANIMATE_TYPE_ALERTBOX	INT	1	0, 1	<ul style="list-style-type: none"> • screen.alertbox API Animation • 0: none Animation • 1: basic Animation
VERTICAL_POS_MESSAGEBOX	INT	-1	-1, 0, n	<ul style="list-style-type: none"> • screen.messagebox API • -1: • 0: • n: 1
VERTICAL_POS_ALERTBOX	INT	-1	-1, 0, n	<ul style="list-style-type: none"> • screen.alertbox API • -1: • 0: • n: 1
ANIMATE_TYPE_GRIDPOPUP	INT	1	0, 1	<ul style="list-style-type: none"> • 가 Animation • 0: none Animation • 1: basic Animation
RANGE_CALENDAR_APPLY_DBLCLICK	BOOL	true	true, false	0 <ul style="list-style-type: none"> • true: • false:
RANGE_CALENDAR_APPLY_ENTERKEY	BOOL	true	true, false	0 <ul style="list-style-type: none"> • true: • false:

RANGE_CALENDAR_APPLY_ACTION	INT	0	0,1,2	0	<ul style="list-style-type: none"> 0: button(), " " 1: focusout, " " 2: calendarclick+focusout, " "
RANGE_CALENDAR_BUTTON_APPLY, RANGE_CALENDAR_BUTTON_DELETE, RANGE_CALENDAR_BUTTON_CANCEL	String	undefined		0: :Apply	<ul style="list-style-type: none"> 0: :Apply 1: :Delete 2: :Cancel
MANDATORYCUSTOMFIELDCLASS, OPTIONALCUSTOMFIELDCLASS, IMPORTANTCUSTOMFIELDCLASS, PROTECTCUSTOMFIELDCLASS, PROTECTMANDATORYCUSTOMFIELDCLASS	String	undefined			apply_inputtypecolor true , / / + / CSS
MANDATORYCUSTOMCHECKCLASS, OPTIONALCUSTOMCHECKCLASS, IMPORTANTCUSTOMCHECKCLASS, PROTECTCUSTOMCHECKCLASS, PROTECTMANDATORYCUSTOMCHECKCLASS	String	undefined			apply_inputtypecolor true , / / + / CSS
MANDATORYCUSTOMRADIOCLASS, OPTIONALCUSTOMRADIOCLASS, IMPORTANTCUSTOMRADIOCLASS, PROTECTCUSTOMRADIOCLASS, PROTECTMANDATORYCUSTOMRADIOCLASS	String	undefined			apply_inputtypecolor true , / / + / CSS
MANDATORYCOLOR, MANDATORYBORDERCOLOR, MANDATORYFORECOLOR	ARRAY	undefined		[255,0,0]	Red, Green, Blue
MANDATORYCOLORFOCUS, MANDATORYBORDERCOLORFOCUS, MANDATORYFORECOLORFOCUS	ARRAY	undefined		[255,0,0]	Red, Green, Blue
OPTIONALCOLOR, OPTIONALBORDERCOLOR, OPTIONALFORECOLOR	ARRAY	undefined		[255,0,0]	Red, Green, Blue
OPTIONALCOLORFOCUS, OPTIONALBORDERCOLORFOCUS, OPTIONALFORECOLORFOCUS	ARRAY	undefined		[255,0,0]	Red, Green, Blue
IMPORTANTCOLOR, IMPORTANTBORDERCOLOR, IMPORTANTFORECOLOR	ARRAY	undefined		[255,0,0]	+ (inputtype_optionkind - 1:important) Red, Green, Blue
IMPORTANTCOLORFOCUS, IMPORTANTBORDERCOLORFOCUS, IMPORTANTFORECOLORFOCUS	ARRAY	undefined		[255,0,0]	+ (inputtype_optionkind - 1:important) Red, Green, Blue
PROTECTCOLOR, PROTECTBORDERCOLOR, PROTECTFORECOLOR	ARRAY	undefined		[255,0,0]	Red, Green, Blue
PROTECTCOLORFOCUS, PROTECTBORDERCOLORFOCUS, PROTECTFORECOLORFOCU	ARRAY	undefined		[255,0,0]	Red, Green, Blue
DISABLECOLOR, DISABLEBORDERCOLOR, DISABLEFORECOLOR	ARRAY	undefined		[255,0,0]	Red, Green, Blue
DATE_CALENDAR_OTHERMONTHDAY	INT	1	1, 2		<ul style="list-style-type: none"> 1: move, / 2: select, 가
DATE_CALENDAR_SIZE	INT	2	0, 1, 2, 3		<ul style="list-style-type: none"> 0: small 1: medium 2: large() 3: xlarge
DATE_SHOWPREVDATE, CALENDAR_SHOWPREVDATE, SCHEDULE_SHOWPREVDATE	INT	1	1, 2		<ul style="list-style-type: none"> shownext true 1: auto(), 1 2: always,
WEEKDAY_COLOR	ARRAY	[3,3,3]			Red, Green, Blue
FRIDAY_COLOR	ARRAY				WEEKDAY_COLOR Red, Green, Blue 가

HOLIDAY_COLOR, SUNDAY_COLOR, SATURDAY_COLOR	ARRAY				Red, Green, Blue
CALENDAR_MIN_YEAR_SELECT	INT	1900			
CALENDAR_MAX_YEAR_SELECT	INT	2050			
HOLIDAY_LIST	ARRAY				<ul style="list-style-type: none"> / (/ , / ,) / : { date: '0101', title: ' ', is_holiday: true }
FIRSTDAY_OF_WEEK	INT	0	0, 1		<ul style="list-style-type: none"> 0: sunday 1: monday
DAYNAME_OF_WEEK, FULL_DAYNAME_OF_WEEK	ARRAY				<ul style="list-style-type: none"> DAYNAME_OF_WEEK : [' ', ' ', ' ', ' ', ' ', ' ', ' '] FULL_DAYNAME_OF_WEEK : [' ', ' ', ' ', ' ', ' ', ' ', ' ']
MONTHNAME_OF_YEAR, FULL_MONTHNAME_OF_YEAR	ARRAY				<ul style="list-style-type: none"> MONTHNAME_OF_YEAR : ['1 ', '2 ', '3 ', '4 ', '5 ', '6 ', '7 ', '8 ', '9 ', '10 ', '11 ', '12 '] FULL_MONTHNAME_OF_YEAR : ['1 ', '2 ', '3 ', '4 ', '5 ', '6 ', '7 ', '8 ', '9 ', '10 ', '11 ', '12 ']
SCHEDULE_DAYNAME_OF_WEEK	ARRAY				<ul style="list-style-type: none"> [' [Sun]', ' [Mon]', ' [Tue]', ' [Wed]', ' [Thu]', ' [Fri]', ' [Sat]']
HTMLEditor_FONT_NAME	ARRAY				<ul style="list-style-type: none"> HTML ['Arial', 'Arial Black', 'Courier New', 'Times New Roman']
HTMLEditor_FONT_SIZE	ARRAY				<ul style="list-style-type: none"> HTML ['1:xx-small:Very small', '2:x-small:A bit small', '3:small:Normal', '4:medium:Medium-large', '5:large:Big', '6:x-large:Very big', '7:xx-large:Maximum'] 1() : ['1:xx-small:Very small', '2:x-small:A bit small'] 2() : ['9px:9 ', '12px:12 '] 3() : ['9px', '12px']
USE_ALERTBOX	BOOL	true	true, false		<ul style="list-style-type: none"> screen.alertbox API AlertDialog false , alert 가
POPOP_UNLOAD_VALUE	STRING				unload API가 , screen_on_popupdestroy result
POPOP_WINCLOSE_VALUE	STRING				result , screen_on_popupdestroy
MAXLENGTH_KEYIN	INT	1	1, 2		<ul style="list-style-type: none"> 1: 2:
MAXLENGTH_INT_TRIMRIGHT	BOOL	false	true, false		<ul style="list-style-type: none"> 가 true: false:
ESCKEY_CLEAR_VALUE	BOOL	false	true, false		ESC
MASK_EDIT_MODE	INT	1	1, 2		<ul style="list-style-type: none"> / mask_editmode) . (1: 2:
MASK_FIT_PATTERN_LENGTH	BOOL	false	true, false		<ul style="list-style-type: none"> false: true:
NORMAL_FIELD_MASK_APPLY	INT	1			<ul style="list-style-type: none"> 1: realtime() 2: focusout

NUMBER_FIELD_MASK_APPLY	INT	1			<ul style="list-style-type: none"> 1: realtime() 2: focusout
NORMAL_FIELD_MASK_DELAY	INT	0			<p>NORMAL_FIELD_MASK_APPLY 가 1 (: ms)</p> <ul style="list-style-type: none"> 1: realtime() 2: focusout
BLANK_PATTERN_ALLOW_MINUS	BOOL	true	true, false		<ul style="list-style-type: none"> true: false:
BLANK_PATTERN_ALLOW_LEADZERO	BOOL	false	true, false		<ul style="list-style-type: none"> true: "0123" → "0123" false: "0123" → "123"
DATE_ALLZERO_IS_VALID	BOOL	false	true, false		<p>0 (: 00000000)</p> <ul style="list-style-type: none"> true: false:
BLANK_MINUS_ONE_CHAR	BOOL	false	true, false		<p>" - " 가</p> <ul style="list-style-type: none"> true: false:
DATE_ALLNINE_IS_VALID	BOOL	false	true, false		<p>9 (: 99999999)</p> <ul style="list-style-type: none"> true: false:
DATE_PARTLENGTH_IS_VALID	BOOL	true	true, false		<p>가</p> <ul style="list-style-type: none"> true: false:
DATE_SELECTBOX_SHOWCLOSEBUTTON	BOOL	false	true, false		
DATE_TODAYBAR_SHOWCLOSEBUTTON	BOOL	false	true, false		
PANEL_BUBBLE_EVENT	INT	1	1, 2		<ul style="list-style-type: none"> 1: ignore() 2: fire()
PANEL_ALLOW_SCROLL	BOOL	true	true, false		<ul style="list-style-type: none"> true: false:
PANEL_FIXED_CONTAINER	INT	1	1, 2		<p>fixed_container 0:default Fixed</p> <ul style="list-style-type: none"> 1: apply() position 2:fixed 2: none() position 2:fixed
PROTECT_COPY	BOOL	false	true, false		<ul style="list-style-type: none"> true: Control C false: Control C
PROTECT_COPY_DISABLE	BOOL	false	true, false		<p>PROTECT_COPY 가 false</p> <ul style="list-style-type: none"> true: Control C false: Control C
PROTECT_COPY_PROTECT	BOOL	false	true, false		<p>PROTECT_COPY 가 false</p> <ul style="list-style-type: none"> true: Control C false: Control C
PROTECT_COOKIE	BOOLEAN	false	true, false		<p>factory.setcookie API</p> <ul style="list-style-type: none"> true: setcookie API false: setcookie API

PASSWORD_POPUPMENU_SHOW	INT	1	1, 2	<ul style="list-style-type: none"> 1: show 2: hide
TAB_RESIZE_CONTENT_BYFOCUS	BOOL	false	true, false	Resize <ul style="list-style-type: none"> true: 가 false: <ul style="list-style-type: none"> fixed_container 0:default Fixed
TAB_FIXED_CONTAINER	INT	1	1, 2	<ul style="list-style-type: none"> 1: apply() position 2:fixed 2: none() position 2:fixed
TAB_ALLOW_USERITEMCHANGE	INT	1	1, 2	가 <ul style="list-style-type: none"> 1: all 가 2: created 3: none 가
TAB_LOCKITEM_XBUTTON_HIDDEN	INT	1	1, 2	lockitem_xbutton_hidden). <ul style="list-style-type: none"> 1: show 2: hidden
TREE_LINESTYLE	INT	1	0, 1	has_lines true , GRID_TREELINESTYLE 가 <ul style="list-style-type: none"> 0: 1: /
PICKLIST_KEYIN_FILTER	BOOL	true	true, false	가
PICKLIST_HIDDENCODE_VALIDATION	BOOL	true	true, false	<ul style="list-style-type: none"> 0: 1:
PICKLIST_COMMENTONLY_INVALIDCODE	INT	2	1, 2	Only 가 Comment <ul style="list-style-type: none"> 1: blank, 2: code(),
PICKLIST_LINKDATA_SYNCPOS	INT	1	1, 2	<ul style="list-style-type: none"> 1: none(), 2: sync,
PICKLIST_KEYIN_FILTER_COMPARE	INT	1	1, 2	<ul style="list-style-type: none"> 1: all(), 2: start,
PICKLIST_KEYIN_FILTER_CASE	INT	1	1, 2	<ul style="list-style-type: none"> 1: ignore(), 2: sensitive,
COMBOBOX_MOUSEWHEEL_ITEMSELECT	INT	1	1, 2, 3	가 <ul style="list-style-type: none"> 1: none 2: focus 가 가 3: always
COMBOBOX_ALLCHECK_TEXTDISPLAY	INT	1	1, 2	<ul style="list-style-type: none"> 1: picklist_selstyle picklist_selstyle 2: allcheckbox_comment 가 allcheckbox_comment

COMBOBOX_ALLCHECK_EVENTTYPE	INT	1	1, 2	<ul style="list-style-type: none"> 1: per-item 2: last-item
COMBOBOX_COMMENTONLY_SETMAXLENGTH	INT	1	1, 2	<p>picklist_selstyle 2:comment only , maxlength</p> <ul style="list-style-type: none"> 1: set input maxlength comment 가 2: unset input maxlength
TEXT_TOOLTIP_TARGET	INT	1	1, 2	<p>/ tooltip, tooltipbox</p> <ul style="list-style-type: none"> 1: component (/) 2: text (/)
INPUT_COPY_DATA_TYPE	INT	1	1, 2	<p>Control+C</p> <ul style="list-style-type: none"> 1: value() 2: display-text
KEYIN_BLOCK_TYPE	INT	1	1, 2	<ul style="list-style-type: none"> 1: keyin (,) 2: value (,)
FOCUS_SELECT_FIELD, FOCUS_SELECT_MULTILINE, FOCUS_SELECT_DATE, FOCUS_SELECT_COMBOBOX, FOCUS_SELECT_SPINNUMBER	INTEGER	1	0, 1, 2	<p>focus_select 0:default ,</p> <ul style="list-style-type: none"> 0: browser(() 1: all(,) 2: none()
XFRAME5BROWSER_MODALLESS_POPUP_WIDTH_GAP, XFRAME5BROWSER_MODALLESS_POPUP_HEIGHT_GAP, XFRAME5BROWSER_BROWSER_WIDTH_GAP, XFRAME5BROWSER_BROWSER_HEIGHT_GAP	INTEGER	0		<p>(74 API)</p> <p>0</p>
CALENDAR_YEAR_GAP_VALUE	INT	0		가 가
CALENDAR_YEAR_GAP_DISPLAY	INT	0		가 가
LOCAL_IP_ADDRESS	STRING			PC IP URL
CALLBACK_~	STRING			"CALLBACK_" 가
DIV_CONTENT_OVERFLOW	INT	1	1, 2	<p>DIV content_overflow 0 ,</p> <p>DOM CSS overflow</p> <ul style="list-style-type: none"> 1: hidden 2: visible
TOOLTIPBOX_GRID_TARGET	INT	1	1, 2	<p>TOOLTIPBOX</p> <ul style="list-style-type: none"> 1: TD() 2: Text()
BUTTON_TOOLTIP_SHOWTYPE, GRID_TOOLTIP_SHOWTYPE	INTEGER	1	1, 2	<p>/ tooltip_showtype</p> <ul style="list-style-type: none"> 1: browser(tooltip) 2: custom(tooltip)
SCREEN_LOADLOG	BOOL	false	true, false	<ul style="list-style-type: none"> true: false:
SCREEN_LOADLOG_SHOWTYPE	INT	0	0, 1, 2	<p>SCREEN_LOADLOG 가 true ,</p> <ul style="list-style-type: none"> 0: 1: 2: CALLBACK_SCREEN_LOADLOG
TABLEVIEW_RWDWIDTH_ONECOLUMN, TABLEVIEW_RWDWIDTH_TWOCOLUMN	INTEGER	0	0/n	<ul style="list-style-type: none"> 0: 1 : 가 , ONW/TWO

TABLEVIEW_RWDWIDTH_FIRSTCOLUMN	INTEGER	150	>10		가 TABLEVIEW_RWDWIDTH_TWOCOLUMN 2 ,
--------------------------------	---------	-----	-----	--	---------------------------------------

From:

<http://technet.softbase.co.kr/wiki/> - **xFrame5 TechNet**

Permanent link:

http://technet.softbase.co.kr/wiki/manual/param/parameter_guide



Last update: **2025/03/19 16:27**